



Leading the Charge.



Panalux Power i4™

With the Panalux Power i4, Panalux is taking another positive step toward reducing diesel-generator running hours, noise pollution, and the emission of nitrogen oxides and particulates. The Panalux Power i4 features an advanced lithium-ion battery array capable of delivering 240V AC power up to a load of 4kW.

The compact size of the Panalux Power i4 makes it ideal for use in remote locations, crane compound during setup, video village, or in public locations where cable runs would create a safety hazard.

Key Features

- Provides power for lights, laptops, tablets, phones, and other auxiliary devices
- Silent, rechargeable lithium-ion battery-powered generator, producing zero emissions
- Perfect companion for features, series, commercials, and photographic shoots
- Built-in LCD display (battery level indicator, output watts, charging time)
- Various power outlet options (16A, 13A, USB)
- Short circuit, over current, over voltage, under voltage, and thermal protection
- Can be utilised as an uninterruptible power supply (UPS)
- Built to meet demands of tough locations
- IP55 rated

Specifications

Outlets	1x 240V AC 16A 2x 240V AC 13A 2x 5V DC 3.1A USB	Operating Conditions	Operating Temperature (discharging): 0°C to +50°C Operating Temperature (charging): 0°C to +45°C
Operational Storage	8.0 kWh Lithium-ion Battery	IP Rating	IP55
Rated Output	Pure Sine Wave 4.0kW Surge Rating: 9.0kW peak	Weight	180kg*
AC Output	Single Phase 240V AC @50Hz	Wheels	Black Diamond Puncture Proof
AC Charging	1x 240V AC 32A In Charging Time (empty to fully charged): 6Hrs*	Dimensions	1155 x 528 x 801 mm (L x W x H)
		Safety	Non-Combustible Sturdy Rollable Frame and Enclosure Conforms to Low Voltage Directive 2014/35/EU Conforms to Electromagnetic Compatibility 2014/30/EU Recommended Storage Temperature: -40°C to +65°C

Overall Dimensions

