

P-5 Wash Light

Specifications		
Optics	Light source	44 x High power 10W RGBW LEDs (6000K)
	LEDs expected lifetime Interchangeable lens option	50,000 hours* 15°, 21° & 43°
Photometric	Light output	23,500 lumen (43° lens)
	Efficacy	58 lm/W
Features	Pan/Tilt	0° / 110°
Electrical	AC Power	208 - 250 V Nominal 50/60 Hz
	Maximum power consumption	440 W (all LEDs on)
	Typical power consumption	410 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	Wireless DMX RDM Stand alone mode (programmable by RFID) Oled graphical display / 5 buttons Software upgradable via Uploader cable (P/N:40500201)
	DMX channels	3, 4, 6, 8, 9 or 10
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glas front
	IP class	IP65 (fan module IP55)
Installation	Mounting	Any, but facing 100% down for permanent installation
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamps included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° – 40°C (14° – 104°F)
	Temperature range, Start-up	-10° – 40°C (14° – 104°F)
	Humidity (max.)	98%
	Cooling	Active, Forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 0.5m with bare ends
Certification	EU Safety	EN60598-1, EN60598-2-17, EN62471
	EU EMC	EN55103-1, EN55103-2
Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega Clamps Wireless DMX G4 antenna User manual Neopren pouch
Fixtures and Accessories	Fixtures	Order no: 80030507 - P-5 Wash Light (43°) Order no: 80030501 - P-5 Wash Light (21°) Order no: 80030508 - P-5 Wash Light (15°)
	Lens/s	Order no: 83061104 - P-5, Lens kit (43°) Order no: 83061103 - P-5, Lens kit (21°) Order no: 83061102 - P-5, Lens kit (15°)
	Brackets	Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket
	Flight case	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)